




---

 PRODUCT-DETAILS

## E219-3CDE

Indicator Light, 16 A, 415 / 230 V AC, 3LED,  
Red / Yellow / Green, MW: 0.5




---

### General Information

Extended Product Type	E219-3CDE
Product ID	2CCA703902R0001
EAN	7612271413323
Catalog Description	Indicator Light, 16 A, 415 / 230 V AC, 3LED, Red / Yellow / Green, MW: 0.5
Long Description	multi indicator light with 3 red, yellow, green LEDs Voltage range = 415-230 VACPDC Module width 0,5

---

### Technical

Rated Voltage ( $U_r$ )	230 V
Rated Operational Voltage	415 / 230 V AC
Rated Insulation Voltage ( $U_i$ )	250 V
Voltage Range	230 ... 415 V AC
Rated Impulse Withstand Voltage ( $U_{imp}$ )	4 kV
Auxiliary Voltage AC/DC	LED Indicator 230...415 V AC

Input Voltage Type	AC
Rated Current (I <sub>n</sub> )	16 A
Rated Frequency (f)	50/60 Hz
Power Loss	0.47-1 W
Power Watt	1.2 W
Number of LEDs	3
Tightening Torque	1.2-1.5 N·m
Lamp Type	LED
Switch Type	Double Interrupting Contacts
Material of Conductor	Copper
Remarks	Sealable in the On and Off positions
Color	Red, yellow, green
Lamp Color	Red / Yellow / Green
Connecting Capacity	Solid 1x1...6 mm <sup>2</sup> Solid 2x2.5 mm <sup>2</sup> Flexible 1x0.75...2x2.5 mm <sup>2</sup>
Service Life	LED Indicator 50000 hour

## Material Compliance

RoHS Information	2CCC441015D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20170426
REACH Declaration	2CCC005047D0201
REACH Information	False - does not contain substances > 0.1 mass percentage
REACH Date	20190425
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

## Environmental

Ambient Air Temperature	Operation -25...+55 °C Storage -40...+70 °C
Degree of Protection	IP20
Environmental Information	2CCC441002C0201

## Technical UL/CSA

Short-Circuit Current Rating (SCCR)	3 kA
-------------------------------------	------

## Dimensions

Width in Number of Modular Spacings	0.5
Product Net Width	9 mm
Product Net Height	85 mm
Product Net Depth / Length	68 mm
Product Net Weight	47 g

Built-In Depth (t <sub>2</sub> )	59 mm
----------------------------------	-------

## Ordering

Package Level 1 Units	box 10 piece
Package Level 1 Gross Weight	528 g
E-Number (Finland)	2312367
E-Number (Norway)	1426461
E-Number (Switzerland)	472551838

## Certificates and Declarations

CB Certificate	9AKK108466A3847
Declaration of Conformity - CE	2CCC441015D0201
Declaration of Conformity - UKCA	9AKK108467A6138
VDE Certificate	9AKK108466A3837

## Installation

Instructions and Manuals	No document needed
--------------------------	--------------------

## Popular Downloads

Data Sheet, Technical Information	2CCC441003C0101
-----------------------------------	-----------------

## External Classifications and Standards

ETIM 8	EC001657 - Indicator light for distribution board
ETIM 9	EC001657 - Indicator light for distribution board
eClass	V11.0 : 27142324
Object Classification Code	P
Standards	EN60068-2-1 EN60068-2-2 EN60068-2-30 DIN EN 62094-1 UL508

---

## Categories

---

Low Voltage Products and Systems → Modular DIN Rail Products → Command and Signalling Devices → Control Switches, Pushbuttons and Indicator Lights → Switches, Pushbuttons and Indicator Lights, E210

