



PRODUCT-DETAILS

# FH202 AC-63/0.03

## Residual Current Circuit Breaker - 2P - Type AC - 30 mA - 63 A



General Information	
Extended Product Type	FH202 AC-63/0.03
Product ID	2CSF202004R1630
EAN	8012542893806
Catalog Description	Residual Current Circuit Breaker - 2P - Type AC - 30 mA - 63 A
Long Description	The RCCBs FH200 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous AC and A types is particularly suitable for installation in domestic applications.

ABB EcoSolutions	
ABB EcoSolutions	Yes
Recyclability Rate of the Product acc. to EN45555	Design for Closing Resource Loops - Standard EN45555 - 72.33 %
ABB Site Meeting Group Waste To Landfill Target	No non-hazardous waste is sent to a landfill UL 2799 Zero Waste To Landfill Validation available
Sustainable Material Content in Packaging (wt. %)	Recycled Paper - 00 % Recycled Cardboard - 20 % Recycled Cardboard - 78 %
Extended Product	Product Durability

## Lifetime

End Of Life Disassembling Instructions	9AKK108469A2269
Environmental Product Declaration - EPD	9AKK108469A6622

## Technical

Type of Residual Current	Type AC
Rated Voltage ( $U_r$ )	230 V
Rated Operational Voltage	230 V
Rated Insulation Voltage ( $U_i$ )	500 V
Rated Impulse Withstand Voltage ( $U_{imp}$ )	4 kV
Rated Current ( $I_n$ )	63 A
Rated Residual Current	30 mA
Rated Conditional Short- Circuit Current ( $I_{nc}$ )	6 kA
Rated Service Short- Circuit Breaking Capacity ( $I_{cs}$ )	1 kA
Maximum Surge Current	0.25 kA
Leakage Current Type	AC
Rated Frequency (f)	50 Hz
Power Loss	at Rated Operating Conditions per Pole 3.2 W
Number of Poles	2P
Number of Modular Spacings per DIN Rail	2
Operating Characteristic	Instantaneous
Mounting Type	DIN-Rail
Options Provided	None
Accessories Available	No
Rated Cross-Section	4 - Multi-Wired 10...25 mm <sup>2</sup> 1 - Solid-Core 25...25 mm <sup>2</sup>

## Material Compliance

RoHS Information	9AKK106713A5603
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20211115
REACH Declaration	9AKK108467A9482
REACH Information	True - contains substances > 0.1 mass percentage
REACH Date	20240429
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

## Environmental

Ambient Air	Operation -5 ... +40 °C
-------------	-------------------------

Temperature	Storage -40 ... +70 °C
Degree of Protection	IP2X
Environmental Information	Refer to RoHS

## Dimensions

Width in Number of Modular Spacings	2
Product Net Width	35 mm
Product Net Height	85 mm
Product Net Depth / Length	69 mm
Product Net Weight	200 g
Built-In Depth (t <sub>2</sub> )	69 mm

## Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.236 kg

## Certificates and Declarations

Declaration of Conformity - CE	9AKK106713A5603
--------------------------------	-----------------

## Installation

Instructions and Manuals	No document needed
--------------------------	--------------------

## Popular Downloads

Data Sheet, Technical Information	2CSC400030D0202
-----------------------------------	-----------------

## External Classifications and Standards

ETIM 8	EC000003 - Residual current circuit breaker (RCCB)
ETIM 9	EC000003 - Residual current circuit breaker (RCCB)
eClass	V11.0 : 27142201
Object Classification Code	F
Standards	IEC/EN 61008

---

## Categories

---

Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs → Residual Current Devices RCDs

